

TECHNICAL DATA SHEET

CODE:	E1DAFO, E25DAFO, E45DAFO & E9DAFO
DESCRIPTION:	FIREOUT DRY POWDER FIRE EXTINGUISHERS AB:E
CATEGORY:	FIRE FIGHTING APPLIANCES - DRY POWDER AB:E
REVISION DATE:	30 JULY 2020

CERTIFIED & APPROVED TO AS/NZS 1841.5

DRY POWDER FIRE EXTINGUISHER FEATURES:

- Deep drawn steel cylinder with welded base and robust skirt
- Powder coated with UV resistant paint finish
- EPDM UV resistant discharge hose with dust cap
- Brass valve with pressure indicator
- 316 stainless steel handles and levers suitable for aggressive environments
- Non-Aluminium Hose Ferrules on 4.5kg & 9.0kg required for underground use
- 316 Stainless steel hose retaining clip and bands on 2.5kg, 4.5kg & 9.0kg models
- Sturdy solid stainless-steel hanging bracket, ideal for aggressive environments are supplied with 4.5 kg and 9.0 kg models
- A rugged epoxy coated metal vehicle bracket comes with 1.0kg & 2.5kg models.
- Aluminium inspection tag and ring (normally removed for underground coal mines)



PRODUCT CODE	CAPACITY	FIRE RATING	AGENT	OPERATING PRESSURE	OPERATING TEMP RANGE	DISCHARGE TIME (APPROX)	DIMENSIONS HEIGHT x DIAMETER	OVERALL MASS (APPROX)
E1DAFO	1.0 kg	2A10B:E	DCP ABE	1500 kpa	-30~65°C	8—11 SEC	340 x 95 mm	1.9 kg
E25DAFO	2.5 kg	3A30B:E	DCP ABE	1500 kpa	-30~65°C	11—14 SEC	400 x 120 mm	3.7 kg
E45DAFO	4.5 kg	6A80B:E	DCP ABE	1500 kpa	-30~65°C	17—20 SEC	510 x 150 mm	7.5 kg
E9DAFO	9.0 kg	10A80B:E	DCP ABE	1500 kpa	-30~65°C	20—23 SEC	590 x 195 mm	13.6 kg

AUSTRALIA WIDE FIRE SUPPLIES ABN 80393915621 UNIT 5/54 PENDLEBURY RD CARDIFF NSW 2285

P:(+61) 02 49540333 E: sales@awfs.com.au W: www.awfs.com.au